



Replace of Hand Pallet Truck

CBD15-W-SE

APPLICATION

Entry level semi electric pallet truck for your new choice, Release the handling strength, reduce the handling cost, decrease manual work.

EASY OPERATING AND MAINTENANCE

1.5t load capacity, the most compact design, electric driving and manual lifting with small turning radius to save the operating and working space. Ergonomic design switch box for accurate and easy operating. Built-in charger, maintenance free battery to reduce the maintenance cost. Assembly components are easy for diagnosis and replacing.

HIGH STABILITY

Leading designed handle switch and controller system, revolutionary to reduce the electronic parts defects rate. Unique drive system with high energy-efficiency to increase the reliability deeply. Fitted with hydraulic pump from HPT, reduce the hydraulic system defects rate. Reverse-back button, emergency stop button, slope antiskid resistance, drive wheel cover to increase the safety of the operator.

SAFETY

Handy emergency disconnect button & durable driving unit ensure working safety.

OPTIONS

- Fork length – 800/915/1000/1070/1100/1300/1400mm
- Fork width – 520/600mm
- Single load wheel
- Lowered fork height for light load – 75mm/40mm(<1000kg)



CE CERTIFICATE



ISO14001:2004



ISO9001:2008

CBD15-W-SE

Distinguishing mark	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.
	1.2	Manufacturer's type designation		CBD15-W-SE
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Semi-electric
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker		pedestrian
	1.5	Load capacity	Q (kg)	1500
Weight	2.1	Service weight	kg	140
Tyres, chassis	3.1	Tyre type		PU
Dimensions	4.4	Lift height	h_3 (mm)	115
	4.15	Fork lowered	h_{13} (mm)	85
	4.19	Overall length	l_1 (mm)	1580
	4.21	Overall width	b_1/b_2 (mm)	560
	4.22	Fork dimensions	$s/e/l$ (mm)	50/150/1150
	4.25	Outside fork width	b_5 (mm)	560/685
	4.34.1	Aisle width,1000×1200 pallet crossways	A_{st} (mm)	1697
	4.34.2	Aisle width,800×1200 pallet crossways	A_{st} (mm)	1697
	4.35	Outer turning radius	W_a (mm)	1380
Performance data	5.1	Travel speed, laden/unladen	km/h	3.5/4
	5.8	Maximum gradeability, laden/ unladen	%	3/6
Electric - engine	6.1	Drive motor rating S_2 60 min	kW	0.65
	6.4	Battery voltage/rated capacity	V/Ah	24/24

Remarks:

The parameters in the table are standard model, for more information, please contact us.
The parameters are subject to change without notice.

