

HS Series Electric Crawler Scissor Lifts

with capacity of 450kg



ZHEJIANG HANGCHA IMP. & EXP. CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com
www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



Download "Hangcha
Forklift" App

2023 VERSION 1/COPYRIGHT 2023/09



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

The World of Hangcha



HANGCHA PROVIDES **5 YEAR**
OR 10000 HOURS GUARANTEE
ON LITHIUM BATTERY.




5 YEAR
WARRANTY

INNOVATIVE SOLUTIONS NEW POWER NOW

Innovative, reliable lithium-ion technology (Lithium Iron-Phosphate), which are developed jointly by HANGCHA and CATL. Battery cells and modules are from CATL, with reliable quality, exclusively for HANGCHA.

- / We use square lithium iron phosphate batteries and modules used in large quantities by commercial vehicles in mature economies.
- / The module uses an aluminum alloy frame which is sturdy, lightweight and with excellent heat dissipation.
- / Safe and effective: Charging efficiency as high as 98%, thermal runaway temperature 600 °C or above.
- / Adapted to low temperatures: Comes standard with an electrical heating feature, ensuring normal operation in low temperatures.
- / Quick charging.
- / Long-working: 4000 charging cycles, capacity retention greater than 80%.
- / Maintenance-free: Battery does not require manual maintenance.
- / Green and clean: Pollution-free, zero emissions.



Rapid charging and opportunity charging ensure continuous availability of vehicles

Allow for fast full charging or boost charging.
They are maintenance free and do not require a battery change when used for multi-shift operations.

TOUGH
EQUIPMENT
FOR TOUGH
APPLICATIONS

HS SERIES

ELECTRIC CRAWLER SCISSOR LIFTS



ELECTROMAGNETIC
BRAKE MAKES IT MOVE
AND STOP FAST.



A REAL STRONG OFF-ROAD ACTOR

HANGCHA HS series of electric crawler scissor lifts , maximum working height is from 6.5m to 13.8m which is excellent for various indoor and outdoor un-leveling ground application.



The machine is moving by the crawler, it has high friction coefficient and high driving strength. Fully sealed permanent magnet synchronous drive motor, it makes fast walking speed, strong power and high efficiency.

The protection class of traveling motor is IP67. Two-wheel drive, the combination of the permanent magnet synchronous motor and high-speed reducer make strong performance.

The machine has an extension platform, the length is about 0.9m, which expands the working space and make the operator feels more comfortable. And the floor of the platform is made of high strength pattern plate with good anti-slip performance.



MOVING MORE



The steering proportional deceleration and electronic differential function can make the machine pivot steering.

1 BUTTON LEVELLING THE HYDRAULIC SUPPORT LEGS



Equipped with one key outrigger leveling function, automatically adjust the frame to the level state, hydraulic outrigger to enhance the stability of the equipment. At the same time, it can also operate a single outrigger to meet the operation requirements under special working conditions.



The scissor cylinder adopts proportional descent control, the moving speed changes gradually with the tilt angle of the operating joystick, and the descent is smooth and comfortable.



Lithium iron phosphate battery with large cell capacity, the total capacity reaches **8kwh**, which supports fast charging.



Comfort

Precise modeling of parameters of permanent magnet synchronous motor closed-loop control, more comfortable control.



Easy maintenance

Drawer design and human-machine interactive control system, easy maintenance.



EASY TO CHARGE

Internal high-power charger can be used by 220V household socket.





STEEL CRAWLER CHASSIS

Full coverage of operation scenarios.

Standard Specification

- / Lithium Battery
- / Internal Charger
- / Permanent Magnet Synchronous Motor
- / Extension platform
- / Pivot Steering
- / Crawler chassis
- / Automatic Braking System
- / Self-Weight Lowering System
- / Oil tube Explosion-Proof System
- / Fault Diagnostic System
- / Charging Protection System
- / Over load Sensing System
- / Automatic Leveling Outriggers
- / Tilt Alarm
- / Motion Alarm
- / Horn
- / Hour Meter
- / Flashing light
- / Manual Emergency Lowering
- / Foldable Guard Rails
- / Emergency Stop Button
- / Self-Locking Gate
- / Charger Indicator
- / Manual Brake Release
- / Safe-belt Attachment Point
- / Tie-Down And Lifting Point

Options

- / Lead-acid Battery
- / Socket device on the basket
- / External Fast charger 380V
- / Working Light



HS Series Electric Crawler Scissor Lifts

Product	Electrical crawler scissor lifts								
	HS0608TP	HS0814TPI	HS1014TPI	HS1214TPI	HS1414TPI	HS0816TPI	HS1016TPI	HS1216TPI	HS1416TPI
01 Model									
02 Maximum working height	m	6.5	8	10	12	13.8	8	10	12
03 Maximum platform height	m	4.5	6	8	10	11.8	6	8	10
04 Length	m	-/1.52	2.72	2.72	2.72	2.72	2.78	2.78	2.78
05 Width	m	0.78	1.4	1.4	1.4	1.4	1.6	1.6	1.6
06 Height (Guardrail Unfolded)	m	2.13	2.39	2.52	2.65	2.78	2.39	2.52	2.65
07 Height (Guardrail Folded)	m	1.76	1.85	1.98	2.11	2.24	1.85	1.98	2.11
08 Platform size	m*m	1.09*0.7	2.27*1.14	2.27*1.14	2.27*1.14	2.27*1.14	2.27*1.14	2.27*1.14	2.27*1.14
09 Extended platform length	m	0.6	0.9	0.9	0.9	0.9	0.9	0.9	0.9
10 Ground distance	m	0.075	0.13	0.13	0.13	0.13	0.13	0.13	0.13
11 Wheel base	m	-	-	-	-	-	-	-	-
12 Maximum load capacity	kg	230	450	450	320	320	450	450	320
13 Maximum load capacity of extended platform	kg	113	113	113	113	113	113	113	113
14 Maximum number of workers(indoor /outdoor)		1/0	2/1	2/1	2/1	2/0	2/2	2/2	2/1
15 Turning radius (inside/outside)	m	Pivot steering	Pivot steering	Pivot steering	Pivot steering	Pivot steering	Pivot steering	Pivot steering	Pivot steering
16 Maximum drive speed(transport mode)	km/h	2	2	2	2	2	2	2	2
17 Maximum drive speed(working mode)	km/h	0	0	0	0	0	0	0	0
18 Maximum slope rating	%	25	30	30	30	30	30	30	30
19 Drive/steering		2×2	2×2	2×2	2×2	2×2	2×2	2×2	2×2
20 Maximum allowable inclination	°	1.7/1.7	1.5/3	1.5/3	1.5/3	1.5/3	1.5/3	1.5/3	1.5/3
21 Tyre	mm	150*72*43crawler	230 Steel rubber crawler						
22 Battery	V/Ah	24/60	80/105 Lithium battery						
23 Weight	kg	860	2470	2650	3050	3340	2870	3050	3450
									3740

