



HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



Download "Hangcha
Forklift" App



ISO45001:2018



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HS SERIES

ELECTRIC CRAWLER SCISSOR LIFT

Work height: 5.9-8.3m

HS SERIES

ELECTRIC CRAWLER SCISSOR LIFT

Efficient and Flexible

- Single-handle control for steering and walking, simple operation.
- It can turn unilaterally and in place, with high maneuverability and flexibility.
- Supports one-click automatic leveling, has strong adaptability to different terrains, and is safe and worry-free.



Low operating costs

- The drawer-type door box structure makes it convenient and quick to inspect and maintain key components.
- Self-diagnosis of faults, intelligent and efficient.



Outstanding performance

- Suitable for various complex terrains.
- Maintenance-free battery with strong endurance.
- Electric drive, zero emissions, high efficiency, maintenance-free for life.



Technical data

| HANGCHA GROUP CO.,LTD. | | | | |
|--|------|---------------------------------|----------------|--------------------------|
| Model | | HS0408TA | HS0608TA | HS0810TA |
| Maximum working height | m | 5.9 | 6.5 | 8.3 |
| Maximum platform height | m | 3.9 | 4.5 | 6.3 |
| Length | m | 1.52 | 1.52 | 2.26 |
| Width | m | 0.83 | 0.83 | 1 |
| Height (Guardrail Unfolded) | m | 2.13 | 2.13 | 2.27 |
| Height (Guardrail Folded) | m | 1.76 | 1.76 | 1.83 |
| Platform size | m*m | 1.29*0.7 | 1.29*0.7 | 1.835*0.9 |
| Extended platform length | m | 0.6 | 0.6 | 0.9 |
| Ground distance | m | 0.075 | 0.075 | 0.09 |
| Wheel base | m | - | - | - |
| Maximum load capacity | kg | 230 | 230 | 255 |
| Maximum load capacity of extended platform | kg | 113 | 113 | 120 |
| Maximum number of workers (indoor/outdoor) | | 2/1 | 1/0 | 2/1 |
| Turning mode | | Pivot steering | Pivot steering | Pivot steering |
| Maximum drive speed (transport mode) | km/h | 2 | 2 | 2 |
| Maximum drive speed (working mode) | km/h | 0 | 0 | 0 |
| Maximum slope rating | % | 25 | 25 | 35 |
| Drive/steering | | 2x2 | 2x2 | 2x2 |
| Maximum allowable inclination | ° | 1.5/3 | 1.5/3 | 2/3 |
| Tyre | mm | 150*72*41 rubber crawler | | 180*72*54 rubber crawler |
| Battery | V/Ah | 24/100 Leadacid; 24/105 lithium | | 24/230lithium |
| Charger | | 24/15 | | 24/30 |
| Weight | kg | 980 | 930 | 2030 |
| Whether equipped with outriggers | | NO | NO | YES |